

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|----|-----|-----------------|-----------|-----|------|
| A | | INITIAL RELEASE | 18DEC2014 | DW | CW |
| B | | ECR-15-013750 | 21SEP2015 | DW | CW |
| B1 | | ECR-15-016224 | 05NOV2015 | DW | CW |
| B2 | | ECR-16-018198 | 09JAN2017 | QY | CW |

M3 SCREW,
RECOMMENDED
TIGHTENING
TORQUE 0.5Nm
M3螺丝, 推荐锁紧力矩0.5Nm


NOTES:

1. TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 250 V
RATED CURRENT: 10 A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 2.5 KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: 0.5-2.5 mm² (20-14 AWG)
CONTACT FINISH: SILVER PLATED
CONTACT TYPE: SCREW CONTACT

注释:

1. 技术参数:
绝缘材料: PC
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 2.5 KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500 次
接线范围: 0.5-2.5 mm² (20-14 AWG)
端子表面处理: 镀银
接线类型: 螺丝连接

TYPE-1:T2010042101-000 TE LOGO
类型-1:T2010042101-000 TE LOGO

| | | | | | |
|--|--|------------------|------------|---|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN | 18DEC2014 |  TE Connectivity | |
| DIMENSIONS: | | DAVID WANG | 18DEC2014 | | |
| mm | | CHK | CHRIS WANG | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD | XU XIANG | | |
| 0 PLC ±- | | PRODUCT SPEC | | NAME | |
| 1 PLC ±- | | 108-137045 | | HA-004-M | |
| 2 PLC ±- | | APPLICATION SPEC | | SIZE | |
| 3 PLC ±- | | 114-137045 | | CAGE CODE | |
| 4 PLC ±- | | WEIGHT | | DRAWING NO | |
| ANGLES ±- | | Customer Drawing | | A300779 | |
| FINISH | | SCALE | | RESTRICTED TO | |
| - | | 2:1 | | - | |
| - | | SHEET | | REV | |
| - | | 1 OF 2 | | B2 | |

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20 BY -

ALL RIGHTS RESERVED.

REVISIONS

| P | LTR | DESCRIPTION | DATE | DWN | APVD |
|---|-----|-------------|------|-----|------|
| - | - | SEE SHEET 1 | - | - | - |
| | | | | | |
| | | | | | |

ALL DIMENSIONS ARE SAME AS TYPE 1,
EXCEPT THOSE DEFINED IN THIS TYPE.
除了在本类型中定义的尺寸外, 其它尺寸同类型 1

NOTES:
SEE SHEET 1
注释:
见页 1

TYPE-2: T2010042101-001 STAINLESS STEEL SCREW, NO LOGO
类型-2: T2010042101-001 不锈钢螺丝, 无LOGO

| | | | |
|-------------------|------------------------|--|----------------|
| T2010042101-001 | HA-004-M | HA-004 MALE INSERT, SIDE OUTLET, TOP LOCK SCREW, STAINLESS STEEL SCREW, NO LOGO HA-004公插, 侧面出线顶部锁螺丝, 不锈钢螺丝, 无LOGO | TYPE-2 类型-2 |
| T2010042101-000 | HA-004-M | HA-004 MALE INSERT, SIDE OUTLET, TOP LOCK SCREW HA-004公插, 侧面出线顶部锁螺丝 | TYPE-1 类型-1 |
| PART NUMBER 料号 | PART DESCRIPTION 描述 | | TYPE 类型 |

| | | | | |
|--|--|--------------------------------|---|--|
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | DWN 18DEC2014 DAVID WANG | | |
| DIMENSIONS: mm | | CHK 18DEC2014 CHRIS WANG | | |
| TOLERANCES UNLESS OTHERWISE SPECIFIED: | | APVD 18DEC2014 XU XIANG | NAME HA-004-M | |
| 0 PLC ±- | | PRODUCT SPEC 108-137045 | SIZE CAGE CODE DRAWING NO RESTRICTED TO | |
| 1 PLC ±- | | APPLICATION SPEC 114-137045 | A300779 © T2010042101000 | |
| 2 PLC ±- | | WEIGHT - | SCALE 2:1 SHEET 2 OF 2 REV B2 | |
| 3 PLC ±- | | Customer Drawing | | |
| 4 PLC ±- | | | | |
| ANGLES ±- | | | | |
| FINISH - | | | | |
| - | | | | |

1470-19 (3/13)