



# DESCO

## WORKSURFACE MAT MATERIALS

### STATFREE T2™ PREMIUM DISSIPATIVE DUAL LAYER RUBBER

| Mat Top Kits            | Beige | Blue  | Dark Grey | Dark Blue |
|-------------------------|-------|-------|-----------|-----------|
| 24" x 36" (0.6m x 0.9m) | 66030 | 66040 | 66050     | 66051     |
| 24" x 48" (0.6m x 1.2m) | 66035 | 66045 | 66055     | 66056     |

Item #14213 Common Point Ground Kit is included with Mat Top Kits.

| Rolls                     | Beige | Blue  | Dark Grey | Dark Blue |
|---------------------------|-------|-------|-----------|-----------|
| 24" x 40' (0.6m x 12.2m)  | 66060 | 66070 | 66080     | 66081     |
| 30" x 40' (0.76m x 12.2m) | 66115 | 66110 | 66105     | 66106     |
| 36" x 40' (0.76m x 12.2m) | 66065 | 66075 | 66085     | 66086     |
| 48" x 40' (1.2m x 12.2m)  | 66090 | 66095 | 66100     | 66101     |

Grounding Hardware is not included with rolls. See pages 20-23 for hardware.

- **Durable rubber material, dissipative on one side and conductive on the other**  
Versatile and long-lasting product; use as a dissipative worksurface table mat. Bottom conductive layer provides reliable path to ground
- **RTT: 10<sup>6</sup> - 10<sup>8</sup> (Dissipative Side) and <10<sup>4</sup> (Conductive Side) Ohms per ESD S4.1**  
Slows charge removal; meets minimum recommended worksurface requirements of ANSI/ESD S20.20 and recommendations of ESD 4.1
- **RTG: 10<sup>6</sup> - 10<sup>8</sup> (Dissipative Side) and <10<sup>4</sup> (Conductive Side) Ohms per ESD S4.1**
- **Thickness: 0.060" (1.5mm)**
- **Made in America**

Drawing PM-104, Technical Bulletin TB-2000

66030,66040, 66050, 66051

Premium Worksurface Mat; Ideal for Soldering or Assembly Areas

Compatible for use with continuous monitors

Look for the Statfree® brand on Desco ESD matting - for your protection and auditing purposes



### STATFREE UC™ DISSIPATIVE DUAL LAYER ULTRA CLEAN RUBBER

| Rolls                                | Blue  |
|--------------------------------------|-------|
| 30" x 40' (0.76m x 12.2m), 2mm thick | 66300 |
| 24" x 30' (0.61m x 9.1m), 6mm thick  | 66340 |
| 30" x 30' (0.76m x 9.1m), 6mm thick  | 66350 |

Grounding Hardware is not included with rolls. See pages 20-23 for hardware.

- **Developed for cleanrooms; minimal outgassing**  
This product was tested by a hi-tech manufacturer who approved it for Class 100 Clean Room use. The FTIR testing producing no detectable levels of Silicone or DOP.
- **RTT: 10<sup>6</sup> - 10<sup>8</sup> (Blue top layer) and <10<sup>6</sup> (Black bottom layer) Ohms per ESD S4.1**  
Slows charge removal; meets minimum recommended worksurface requirements of ANSI/ESD S20.20, recommendations of ESD 4.1 a
- **Thickness: 0.080" (2mm), 0.250" (6mm)**
- **Proprietary product**

Drawing PM-121, Technical Bulletin TB-2000

For detailed information on all Desco worksurface mats: [www.desco.com/catalog](http://www.desco.com/catalog)

Compatible for use with continuous monitors



### STATFREE J™ DISSIPATIVE SHOCK RESISTANT FOAM RUBBER

| Mat Top Kit             | Black |
|-------------------------|-------|
| 16" x 24" (0.4m x 0.6m) | 45010 |

| Roll                     | Black |
|--------------------------|-------|
| 24" x 40' (0.6m x 12.2m) | 45000 |

Grounding Hardware is not included with rolls. See pages 20-23 for hardware.

- **Resilient non-skid natural foam rubber**  
Perfect for cafeteria trays and cart shelves
- **Custom sizes available**  
To fit your application
- **RTT: 10<sup>5</sup> - 10<sup>7</sup> Ohms per ESD-S4.1**
- **RTG: 10<sup>5</sup> - 10<sup>7</sup> Ohms per ESD-S4.1**
- **Thickness: 0.125" (3.2mm)**
- **Made in America**

Drawing PM-114, Technical Bulletin TB-2000

ESD Cushioning Protects Fragile Parts



See our products being Made in America on our web site: [www.desco.com/factory](http://www.desco.com/factory)



45010